

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (original) A facsimile monitoring system comprising:

b1 a facsimile having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring software for monitoring a state of a memory transmission file of the facsimile,

wherein, when a memory transmission by the facsimile is completed, a message of a completion thereof is displayed on a displaying panel of said personal computer immediately thereafter.

2. (original) A facsimile monitoring system comprising:

a facsimile having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring software for monitoring a state of a memory transmission file of said facsimile,

wherein, when there exists a communication error by the facsimile a message of an alarm is displayed on a displaying panel of said personal computer immediately thereafter.

3. (original) A facsimile monitoring system comprising:

a facsimile device having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring a state of a memory transmission file of said facsimile device,

wherein, when there exists a file in said facsimile device indicating a communication error, said file of communication error can be deleted using said personal computer.

4. (original) A facsimile monitoring system comprising:

a facsimile device having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile device and including monitoring software for monitoring a state of a memory transmission file of said facsimile device,

wherein, when there exists a file in said facsimile device indicating a communication error, an address of said communication error file and a transmission property thereof can be changed from said personal computer.

5. (original) A facsimile monitoring system comprising:

a facsimile device having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring software for monitoring a state of a memory transmission file of said facsimile device,

wherein, when there exists a file in said facsimile device indicating a communication error, at least one of an address of said communication error file and a transmission property thereof can be

changed from said personal computer.

6. (currently amended) A method of monitoring a facsimile device comprising the steps of:

monitoring a state of a memory transmission of said facsimile device; and

displaying a message of a completion of the memory transmission on a ~~displaying panel for~~ display of a personal computer connected to the facsimile device, immediately after the memory transmission is completed.

7. (currently amended) A method of monitoring a facsimile device comprising the steps of:

monitoring a state of a memory transmission file of said facsimile; and

displaying an error message indicating a communication error in the memory transmission on a ~~displaying panel for~~ display of a personal computer connected to the facsimile device, immediately after the communication error occurs.

8. (original) A method of monitoring a facsimile device comprising the steps of:

monitoring a state of a memory transmission file of said facsimile device; and

deleting a file indicating a communication error in said facsimile device from a personal computer, when there exists a file indicating the communication error.

9. (original) A method of monitoring a facsimile device comprising the steps of:

monitoring a state of a memory transmission of said facsimile device; and

changing an address in a communication error file and a transmission property thereof from a personal computer, when there exists the communication error file.

10. (original) A method of monitoring a facsimile device comprising the steps of:

monitoring a state of a memory transmission of said facsimile device; and

changing an address in a communication error file and a transmission property thereof from a personal computer, when there exists the communication error file.

11. (currently amended) A facsimile device monitoring system for monitoring a communication result of a facsimile device from an external terminal, comprising:

a facsimile device provided with a result sending-out medium sending out a communication result to an external terminal[[,]]; and

an external terminal provided with


a display medium displaying and outputting the communication result sent from said facsimile device, and

a result monitoring medium executing an operation of ~~sending out a result of~~ monitoring the communication performed by result from

said result sending-out medium of said facsimile device ~~to~~ and causing
said communication result to be displayed on said display medium of
said external terminal ~~periodically~~ immediately thereafter.

12. (original) The facsimile device monitoring system as defined in claim 11,

wherein said result monitoring medium monitors a state of a memory transmission file of said facsimile device, and

 wherein said result monitoring medium sends out a completion result or an error result of the memory transmission to said external terminal, and

wherein said external terminal outputs a completion message or an alarm message as a completion result or an error result.

13. (original) The facsimile device monitoring system as defined in claim 11,

wherein said external terminal is provided with an indication medium for designating a transmission file to be held in memory of said facsimile device and for indicating treatment of said transmission file, and further comprising:

a file treatment medium for treating the file in the memory of said facsimile device on a basis of the indication from said indication medium.

14. (original) The facsimile device monitoring system as defined in claim 12,

wherein said external terminal is provided with an indication

medium designating the transmission file to be held in a memory of said facsimile device and indicating a treatment of said transmission file, and further comprising:

a file treatment medium for treating the file in the memory of said facsimile device on the basis of the indication from said indication medium.

15. (original) The facsimile device monitoring system as defined in claim 13,

wherein said file treatment medium deletes a transmission error file designated on a basis of the indication transmitted by said indication medium, from the memory of said facsimile device.

16. (original) The facsimile device monitoring system as defined in claim 14,

wherein said file treatment medium deletes a transmission error file designated on a basis of the indication transmitted by said indication medium from the memory of said facsimile device.

17. (original) The facsimile device monitoring system as defined in claim 14,

wherein said file treatment medium deletes a transmission error file designated on a basis of the indication transmitted by said indication medium from the memory of said facsimile device.

18. (currently amended) The facsimile device monitoring system as defined in claim 14,

Keizou BABA, S.N. 09/448,885
Page 8

Dkt. No. 2271/60735

wherein said file treatment medium changes one or ~~more~~ more of an
(b) address of the designated transmission error file and a transmission
property.
